

Dalapro Lightning Facade

Product information

Dalapro Lightning Facade is a ready-to-use lightweight spray filler for minor repairs outdoors (holes and cracks on mineral substrates) but can also be used for indoor plastering on most common substrates.

The product is manufactured in accordance with ISO 9001 and ISO 14001.

Instructions

Apply by spraying or by hand on clean, dry and firmly attached surfaces at a minimum temperature of +5° C. Use sandpaper, particle size 100-120, when sanding the dry surface. Eye protection and dust mask are recommended when sanding. Filled surfaces should be primed before wallpapering.

Follow your local branch regulations and recommendations.

Consumption of material

Thin coat plastering = 1 litre/m² per mm

Drying time

The drying time is dependent on substrate, layer thickness, temperature, ventilation and atmospheric conditions.

Storage

Protect from frost and direct sunlight. The packaging is marked with best-before date. Unopened packs can be stored in 12 months.

The information contained in this data sheet is the result of our study and experience. It is offered in good faith and cannot a guarantee and no liability is assumed. We reserve the right to change any product information included in this document without prior information.

For latest product information: www.dalapro.com

Last updated 2017-02-14

TECHNICAL DATA

Binder

Latex co-polymer

Solvent

Water

Filler

Microspheres and white dolomite

Particle size

Max. 0.2 mm

Bulk density

Approx. 0.8 kg/litre

Vol. non-volatile matter

Approx. 67%

pH

Approx. 9

Colour

Grey

Build

Very high (> 5 mm)

Flammability

Does not spread or support fire

Cleaning

Use water for tools and spillage

Packaging

15 l plastic bag

Range of application

For in- and outdoor use

